



WPC M SEALER

TECHNICAL DATA SHEET

1.Product Description:

WPC M SEALER is a Vinyl Acrylic water based wall sealer. It is specially formulated for economical needs.

2.Recommended Uses:

For interior walls, ceilings, plaster, brickwork, hard and soft boards and asbestos.

3.Composition:

Pigments	: Mainly Titanium Dioxide, Iron Oxide, Carbon Black, Organic Pigments and Mineral Extender
Binder	: Vinyl Acrylic Copolymer Emulsion
Thinner	: Water
Properties	
Color	: A wide range of colours.
Appearance	: Flat Matt

4. Recommended no. of coats : 1 Coats

Recommended Dry Film Thickness Per Coat	: Around 30 µm (Dependent on the substrate condition)
Drying Time	
Touch Dry	: 15 minutes (dependent on temperature and humidity)
Hard Dry	: 1 hour
Recoating Interval	: 1-2 hour
Theoretical Coverage at Recommended Dry Film Thickness	: 10 - 13 m ² per litre per coat (Actual coverage is dependent on substrate condition.) *

5. Application Methods:

Brush / Roller : Dilute the paint with not more than 5% of water.

6. Clean Up : Clean up equipment with water immediately after use.



WPC M SEALER

TECHNICAL DATA SHEET

7. Surface Preparation:

Remove all loose, defective paint or powdery residues. Repair cracks, uneven surfaces with Putty or suitable fillers. Smoothen the putty / filler areas with sandpaper. Surfaces to be painted must be cleaned thoroughly and dry, it must be free from dirt, grease and other foreign matters. Allow all surfaces to dry completely prior to painting. Avoid painting when the moisture content and alkalinity of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 16% measured by protimeter and alkalinity of the walls to be below pH9.)

8. Previously Painted Surfaces

Remove all loose, defective paint or powdery residues, loose chalk, dust and foreign matter. Repair cracks uneven surfaces with Multi Purpose Joint Compound or suitable fillers. Smooth the putty / filler areas with sand paper. Surfaces to be painted must be cleaned thoroughly and dry, it must be free from dirt, greaaw and other foreign matters. Allow all surfaces to dry completely prior to painting. Avoid painting when the moisture content and alkalinity of the walls are still high.

9. Recommended Paint System

Type of Substrate	: For Masonry
Sequence	
Sealer	: WPC M Sealer – 1 Coat
Finish	: WPC M-Tex Color Creations – 2 Coats

10. Standard Packing : 7 litres, 18 Litres

11. Safety, Health and Environmental Information:

Keep container tightly closed and keep out of reach of children or away from food and drink.
Ensure good ventilation during application and drying.
When applying paint, it is advisable to wear eye protection.
In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
Remove splashes from skin by using soap or water.
Paint must always be stored in a cool place.
When transporting paint, care must be taken. Always keep container in a secure upright position.
Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.